



MATERIAL: EPOXY RESIN BONDED GLASS FIBRE LAMINATE SHEET TO BS.4584 Pt.3 TYPE FR4. MATERIAL MUST CONFORM TO UL94V-0. COPPER PLATING TO BE 1oz MIN (35um) FINISHED THICKNESS 1.6mm / 1/16". DOUBLE-SIDED COPPER. BOARD SIZE 190.0mm BY 140.0mm.

FINISH: HASL
SOLDER RESIST REQUIRED ON SOLDER SIDE
SILKSCREEN IN WHITE

LAYER BUILD

- TOP SILK SCREEN
- COMMON SOLDER RESIST
- COMPONENT SIDE COPPER
- SOLDER SIDE COPPER
- COMMON SOLDER RESIST

REF.	FINISHED DIA - mm	QUANTITY	PLATED
A	0.8	98	YES
B	1.1	16	YES
C	1.3	20	YES
D	4.0	4	NO
E			
UNREF	1.0	672	YES

Baldwin PCB Design mikebaldwinpcbdesign.co.uk		01825 782108	
Customer		GREG FORDYCE	
Title		16 CELL SLAVE BOARD	
GOMBERG PCB DESIGN		V1.0	07/11/09
GOMBERG PCB DESIGN		Issue	Date



www.021825.gomberg.com

16 CELL SLAVE BOARD V1.0